



**Supermarine**  
Marine Paint

P. O. Box 3007, Arlington WA. 98223  
360-651-9050 FAX 360-651-2540  
info@topsecretcoatings.com  
www.topsecretcoatings.com

---

## SM-600 Super-Spar Marine Spar Varnish

SM-600

### Get On Board!

Super-Spar Marine Spar Varnish features a government spec formula that out performs typical "dealer" brands in every significant performance category. A superior product that conforms to government specification number AA-1800 so you know you are getting the best!

Super-Spar utilizes the finest tung-oil and phenolic modified resins available, two materials when combined have a natural immunity to ultra violet rays. We've added high quality UV blockers and absorbers to enhance its protective qualities. It protects and beautifies marine woods from extremes in weather, saltwater and intense UV while allowing the texture, grain and beauty of wood show through. The finish is resistant to peeling and cracking topside or in the cabin. It offers a good combination of hardness and a high level of flexibility. It is excellent for quick touch ups and repairing scrapes and dings and it is easy to use.

Apply it with confidence on teak, oak, mahogany, and a variety of wooden substrates. It is acceptable for use on most all metals. It produces a clear natural looking, glossy protective finish. Use it on wooden decks, doors, trim, in on paneling, cabinets and furniture. It can be brushes, rolled or sprayed. Two to three coats or more are recommended for best results on untreated wood. Gloss finish.

#### **Product Features:**

- Acceptable for use on wood or metal.
- Produces a film remains both hard and flexible at the same.
- Self leveling formula reduces brush and roller marks.
- Less likely to crack or fade.
- Finish is remarkably smooth and soft in appearance.
- Superior UV resistance.
- Easy to repair.
- Withstands extremes in temperature.
- Buffing removes mars and abrasions.

# **PERFORMANCE DATA**

## **SM-600 Super-Spar Marine Spar Varnish**

**COLOR(S):** Clear Gloss.

**PRODUCT TYPE:** Air Drying, Alkyd Varnish.

**DESCRIPTION:** Super-Spar Marine Spar Varnish combines toughness and durability with ease of performance. It gives maximum protection from all marine elements such as sun, salt air and water. Conforms to government specification number A-A-1800.

**Intended Use:** For interior or exterior wood and metal surfaces.

### **PHYSICAL CHARACTERISTICS**

**VISCOSITY:** 60-65" (FORD #4)

**DRY TO TOUCH:** 2 hours

**WEIGHT SOLIDS:** 52-54%

**TACK FREE:** 10 hours

**VOLUME SOLIDS:** 46-48%

**TIME TO RECOAT:** Overnight

**WEIGHT PER GALLON:** 7.70 lbs. per gal.

**DRY HARD:** 8 hours

**V.O.C.:** 420 grams per liter

**COLOR RANGE:** Clear

**FLASH POINT:** 105° F.

**PACKAGING:** Qt., 1 or 5 gallon containers

**PRACTICAL COVERAGE:** 400-600 square feet per gallon.

**SURFACE PREPARATION:** All surfaces to be coated must be thoroughly cleaned and free from grease, wax, dirt, oil, dust and alkali before application of Super-Spar.

**APPLICATION:** Apply varnish directly from the can with a clean brush. Allow to dry overnight. Sand and, using a tack rag, dust off carefully before applying second coat. Do not varnish in damp, cold or frosty weather as this will affect the gloss. It is preferable to varnish after the morning dew has dissipated and finish well before dusk.

**THIN & CLEAN UP:** Use SM-101 Leveling Thinner.